



Recolorezzo **SPHERA**
Decorative Plaster



Recolorezzo SPHERA Decorative Plaster



CHARACTERISTICS

Produces pearly effect with small fine spheres.

Its alkalinity is high, and it does not form any blisters and cracks. Although waterproof from the outside to the inside, it allows the walls to breathe, drawing the moisture from the inner side. It is water-based and not dangerous to the human health and the environment. The area of application smells very pleasantly thanks to the plaster's perfume characteristic.

AREAS OF APPLICATION

The plaster can be applied to mineral surfaces such as black coat, concrete, cement board, gypsum plaster, plasterboard, fixed sheet metal and old painted surfaces on both interior and exterior facades.

SURFACE PREPARATION

Once the intended application surfaces have been cleaned of any dirt, oils, swollen paint and dust, the defects on the inside surface must be corrected with putty.

It is advisable to use a background paint-base with the same color as the one of the selected plaster.

APPLICATION INSTRUCTIONS

SPHERA must be mixed to a homogeneous state.

After the lower base layer is completely dry, use a RECOLOREZZO brush-spatter and a mortar-board to gently apply SPHERA to the surface as first layer. Depending on customer's wish, a second layer can be applied, which will make the spheres /plaster structure/ more saturated.

During the application, as well as 24 hours after it has ended, the ambient temperature must be at least +5°C and no more than +35°C.

APPLICATION METHOD

SPHERA can be applied in several ways – vertical effect, horizontal, diagonal and chaotic. Use several colors and a combination of other RECOLOREZZO plasters if you want to achieve an interesting and artistic effect.

Recolorezzo SPHERA Decorative Plaster



TECHNICAL PARAMETERS

DENSITY (GR/CM ³)	1,68 + 0,02
VISCOSITY (KREBS UNITS OF MEASUREMENT)	„Viscos“
FLASH POINT	Water-based
PH	12-14
SOLID SUBSTANCE (% WT)	73 + 2
THEORETICALLY CALCULATED VOLATILE ORGANIC COMPOUNDS (GR/LITER) <small>(EUROPEAN UNION DIRECTIVE N° 2004/42/EC)</small>	40
DILUTION	none
COLOR	According to the Recolorezzo Silk palette
THEORETICAL CONSUMPTION* (GR/M ²) (FOR A SINGLE COAT)	200-300
COVERING POWER (M ² /KG)	5 - 6
DRYING TIME (AT 23°C)	Time without touching: 5 hours. Period of complete drying: 24 hours.
SHELF LIFE**	2 years
PACKAGING	1 kg and 2,5 kg

*Consumption theoretical values: For one coat depending on surface smoothness, absorbency and application techniques.

**Shelf life: According to storage conditions between +5°C and +35°C, in unopened packaging, in a cool and dry place, protected from direct sunlight.

HAZARD WARNINGS

H318: Causes serious eye damage.

SAFETY MEASURES

P102: To be stored in a place that is inaccessible to children.

P280: Wear protective gloves, protective clothing, safety glasses and face protection.

P302+P352: IN THE EVENT OF SKIN CONTACT: Wash with soap and use plenty of water.

P332+P313: IN THE EVENT OF IRRITATED SKIN: Consult a doctor.

P301+P310: IN THE EVENT OF SWALLOWING: CONTACT YOUR LOCAL HEALTH CENTER FOR ASSISTANCE or call a doctor.

P305+P351+P338: IN THE EVENT OF EYE CONTACT: Rinse gently with water for several minutes.

If you have contact lenses, please remove them and continue rinsing.

Do not use the product packaging for food storage.